

NASA TECH BRIEF

NASA Pasadena Office



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Design Method for Minimizing RF Voltage Breakdown

Voltage breakdown in RF components produces a disruption or loss of communication and, occasionally, damage to the components. In RF voltage breakdown, there are two main electron-generation mechanisms: (1) the ionization of gas by electron collision and (2) secondary electron emission from electrodes. At gas pressures generally above 10^{-2} torr, the electron mean free path is shorter than the electrode-separation distance, and ionization by electron collision becomes the primary source of breakdown. On the other hand, at pressures below 10^{-2} torr, the electron mean free path is longer than the electrode-separation distance, and the primary generation mechanism, for RF voltage breakdown is secondary emission. The latter is known as multipacting.

To obtain further insight into RF voltage breakdown, a research study was conducted and the results were published in the "Final Report on RF Voltage Breakdown in Coaxial Transmission Lines" (JPL Technical Report 32-1500). In the report, multipacting and ionization breakdown, involving common coaxial transmission lines and the parallel-plate configuration, are discussed. The lines discussed are 50-, 74-, 91-, 132.5-, and 174-ohm impedance types. The frequency range includes the commonly-used transmission bands from approximately 1 MHz up to K-band. Data are presented

for both the breakdown voltage and the breakdown power, as a function of frequency, and the inner-to-outer conductor distances.

Using the principles of similarity and a minimum of experimental data, a number of universal curves have been constructed covering a wide range of experimental parameters. Gases other than air, such as argon and carbon dioxide, also are included in the study.

Notes:

1. The data presented in the report are sufficient to determine the power-handling capability of all the common coaxial transmission lines and uniform field geometries encountered by RF design engineers.
2. Requests for further information may be directed to:

Technology Utilization Officer
NASA Pasadena Office
4800 Oak Grove Drive
Pasadena, California 91103
Reference: TSP73-10520

Source: Richard T. Woo of
Caltech/JPL
under contract to
NASA Pasadena Office
(NPO-13408)